

revolution RFP8

Four - Post Lift / 8,000 lbs. capacity

FEATURES:

- Single point lock release
- Adjustable lock ladder
- Multi-position locks allow runways to be level at any lock position
- Standard 115V plug provided

**72" LIFTING
HEIGHT**

**68"
CLEARANCE
UNDER RUNWAYS**



Model Shown: RFP8P000
8,000 lbs. capacity
Available in black only



Gold Certified

Revolution's RFP8 is ALI Certified. This lift meets the highest industry safety and performance standards. Look for the Gold label.


DOUBLE YOUR PARKING SPACE INSTANTLY!

Specifications	RFP8
Capacity	8,000 lbs. (3629kg)
Rise	72" (1829mm)
Overall length with approach ramps	207'-1/2" (5270mm)
Overall length without approach ramps	175'-1/2" (4458mm)
Overall width w/o motor	103'-1/2" (2629mm)
Approach ramp Length	32" (813mm)
Runway width	18'-1/2" (470mm)
Runway length	169'-1/2" (4305mm)
Runway height	4'-1/2" (114mm)
Height of columns	81'-1/2" (2070mm)
Clearance between columns	94" (2388mm)
Clearance between runways	38" (965mm)
Outside runway to outside runway	75" (1905mm)
Clearance under runway	68" (1727mm)
Motor specs	110VAC, 1HP

FEATURES:

- 68" (1727mm) clearance under runways at full stroke
- Runway length: 13'-10" (4216mm)
- Overall length with ramps: 17'-4" (5283mm)
- Overall width without motor: 8'-6-1/2" (2603mm)
- Steel approach ramps
- Durable powder coat finish
- Available in black only

LIFT INCLUDES:



Jack Tray



Three (3) Drip Trays



Poly Caster Kit

For help in calculating your required ceiling height, go to www.revolutionlift.com and click on **LIFT SELECTION GUIDE.**

revolution

www.revolutionlift.com

- 2700 Lanier Drive Madison, IN 47250
- phone: 812.273.1622 ■ sales@revolutionlift.com

revolution RFP9

Four - Post Lift / 9,000 lbs. capacity



FEATURES:

- Single point lock release
- Adjustable lock ladder
- Multi-position locks allow runways to be level at any lock position

**84" LIFTING
HEIGHT**

**79-1/4"
CLEARANCE
UNDER RUNWAYS**

PERFECT FOR HOME USE!

FEATURES:

- Standard 115V plug provided
- 6'-7-1/4" (1727mm) clearance under runways at full stroke
- Runway length: 15'-8" (4775mm)
- Overall length with ramps: 18'-9-1/2" (5728mm)
- Overall width without motor: 10'-1" (3073mm)
- Steel approach ramps
- Durable powder coat finish
- Available in black only
- Optional lightweight aluminum ramps available

For help in calculating your required ceiling height, go to www.revolutionlift.com and click on **LIFT SELECTION GUIDE**.

revolution
www.revolutionlift.com

- 2700 Lanier Drive Madison, IN 47250
- phone: 812.273.1622 ■ sales@revolutionlift.com




Lit# REVOLUTION RFP8_RFP9 cutsheet_2016.07
©2016 Vehicle Service Group™. Printed in the U.S.A., All Rights Reserved.
Unless otherwise indicated, Revolution Lift®, Vehicle Service Group™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.



Model Shown: RFP9P000
9,000 lbs. capacity
Available in black only

LIFT INCLUDES:



Jack Tray



Four (4) Drip Trays



Poly Caster Kit

Gold Certified

Revolution's RFP9 is ALI Certified. This lift meets the highest industry safety and performance standards. Look for the Gold label.

Specifications	RFP9
Capacity	9,000 lbs. (4082kg)
Rise	84" (2134mm)
Overall length with approach ramps	225 - 1/2" (5728mm)
Overall length without approach ramps	192 - 1/2" (4889mm)
Overall width w/o motor	121" (3073mm)
Approach ramp Length	36 - 1/4" (921mm)
Runway width	21 - 1/2" (546mm)
Runway length	184" (4674mm)
Runway height	4 - 3/4" (121mm)
Height of columns	97" (2464mm)
Clearance between columns	109 - 1/2" (2781mm)
Clearance between runways	39" (991mm)
Outside runway to outside runway	82" (2083mm)
Clearance under runway	79 - 1/4" (2013mm)
Motor specs	110VAC, 1HP